

MULTI SPORTS



ARGES Reflex Photocell

Overview



ARGES Reflex Photocell, front view with its optional Deluxe support, along with the photocell reflector

The ARGES Reflex Photocell consists of a transmitter and a reflector unit. The transmitter produces an infrared beam that is reflected on the photocell reflector, which serves as a mirror when correctly aligned opposite. Anything or anyone that crosses the field of the beam creates an interruption which is instantly reported to a timing device accordingly to meet the International Sport Federations standards. The ARGES Reflex Photocell allows a simple and constant monitoring of the cell alignment. It features an internal and accessible battery lodging and can also be connected to an external battery or a DC power supply. The two outputs contacts allow to connect the ARGES to two different timing devices simultaneously (main & back-up for example). The new ARGES Reflex Photocell also features a completely accessible DIL switch panel on the side of the photocell allowing users to choose from the many operating modes and options. The ARGES Reflex Photocell is a highly precise and reliable timing device even in extreme meteorological conditions and temperatures.

Top features

- Distance between cell and reflector up to 30 m
- 2 non-polarized output contacts
- Interruption auto detection
- Maximum security
- Easy monitoring
- Internal or external battery or DC supply
- Battery level and receiver signal level indicator
- Meet the FIS & FEI standards
- Pulse duration selector (1ms, 100 ms or beam signal)
- Normally open/Normally close contact selector

Available types & options

3459.900: ARGES photocell, no support


3459.910: ARGES photocell, ball head support

3459.920: ARGES photocell, 2 axis support

Connections and UI

- 1 ON/OFF switch
- 2 Rotary push/switch button
- 3 4 LEDs indicator (battery level & reception power signal level)
- 4 Output contact 1
- 5 Output contact 2, external power input & alignment level

Specifications

Article number :	3459.900
Battery type :	3xAA or UM-3
Average battery life :	~ 20h (with alkaline batteries)
Battery indicator :	4 levels battery symbol
Dimensions :	188 x 57 x 95 mm
Photocell weight :	915 g (incl. batteries)
Reflector weight :	160 g
Fixing :	UNC 1/4" mounting thread
Operating temperature :	-30°C to 70°C
Storage temperature :	-40°C to 85°C
Operating distance :	up to 30m
Response time :	< 1 ms sensing time
Relative humidity :	up to 95% (non-condensing)
Protection class :	IP54
Certifications :	CE and  RoHS compliant



All the information contained in this document can be modified without warning. Swiss Timing LTD cannot be made responsible for any errors contained in this document or any damage secondary or consequent (including the loss of profits) arising from the supplying, performance or use of this product, wether it be on the base of a guarantee, a contract or any other legal ground.

3459.900.00 - B

SWISS TIMING LTD

A COMPANY OF THE  SWATCH GROUP

P.O. Box 138, Rue de l'Envers 1
CH-2606 Corgémont - Switzerland
www.swisstiming.com

Phone +41 32 488 36 11
Fax +41 32 488 36 09
info@swisstiming.com